

Series

GASTRO

HIGH-TECH

HIGH-PERFORMANCE COMPETENCE

Whether a small-sized system for a bar or a central installation for canteen kitchens and hotel business, the GASTRO series offers flexibility for your individual water demand. Space-saving and easy to install, the low-maintenance operation allows a hygienic and carefree water supply to your equipment.

FREELY ADJUSTABLE WATER HARDNESS

As a powerful central multisystem, multiple recipients, for example a pot rinser, a steamer, a coffee machine and many more, can comfortably be supplied with hygienic, clean water. Thereby the water hardness range of individual devices can be freely adjusted and read off the display according to your personal wish. This is a big advantage for your coffee machines: the manufacturers' recommendations can be complied and they guarantee an exclusive taste.

ADAPTABLE AND FLEXIBLE

Should your water needs increase, you can expand your system thanks to the practical modular design of the GASTRO series at any time. Whether throughput or tank size: you choose the optimal system for you



EASYRO[®]

GASTRO

BASIC



Control unit with display

STANDARD



Control unit with display

LARGE



ELECTRICAL CONNECTION	BASIC	STANDARD	LARGE
System	EASYRO 150	EASYRO 300	EASYRO 600
Power draw	250 W	250 W	600 W
Voltage	230V AC/50 Hz	230V AC/50 Hz	230V AC/50 Hz
Noise level	>60 dB(A)	>60 dB(A)	>60 dB(A)
Fuse	10 A	12 A	16 A

WATER CONNECTION

Line requirement	10 l/min	15 l/min	20 l/min
Line pressure	2-6 bar	2-6 bar	2-6 bar
Unit connection	3/4" outer thread	3/4" outer thread	3/4" outer thread
Waste water connection	JG 10/DN 20	JG 10/DN 20	JG 10/DN 20

HYDRAULIC CAPACITY

Capacity (24-hrs)	2400 L	4800 L	9600 L
Pump output pressure	1-5,5 bar	1-5,5 bar	1-5,5 bar
Standard pressure tank	19 L	200 L	200 L

SYSTEM DATA

Prefilter external, 2-stages	YES	/	/
Wall panel incl. prefilter (H/D/W)	/	330/500/500	330/500/500
Desalination rate min.	95%	95%	95%
Waste water * min.	35%	35%	35%
Drains	2 x JG 10	2 x JG 10	2 x JG 10
Drain 1	Supply water, fixed		
Drain 2	Adjustable 0-200 µS/cm ¹		
Weight, empty	Approx. 16 kg	Approx. 20 kg	Approx. 40 kg
Dimensions (H/D/W)	140/450/460 mm	280/450/460 mm	560/450/460 mm

* Depending on the raw water quality and membrane service life.

STANDARD EQUIPMENT

Mounting set	1	1	1
--------------	---	---	---

SYSTEM DATA TANK (optional expandable)

PERMEAT - TANK



Capacity	19 L	60 L	100 L	200 L	500 L	1000 L
Type	Pressure tank	Pressure tank	Pressure tank	Pressure tank	pressureless**	pressureless**
Fill level man.	/	/	/	/	incl.	incl.
Pressure indicator	/	/	incl.	incl.	/	/
Dimensions (Ø/H) (H/D/W)	Ø 270 H 400mm	Ø 380 H 850mm	Ø 450 H 965mm	Ø 550 H 1255mm	800/1055/870mm	1700/1055/870mm
Monitoring min/max	/	/	/	/	incl.	incl.

** incl. pressure pump Hydrojet JP5 with dry run protection (techn. data s. data sheet)