



VIEW MORE

EASYRO®

Water treatment for demanding production processes.



EASYRO® 150

Output (24 hr) 2.400 l
Weight, empty 18 kg
Power consumption 250 W
L/W/H 450/490/147 mm



EASYRO® 300

Output (24 hr) 4.800 l
Weight, empty 25 kg
Power consumption 250 W
L/W/H 450/490/284 mm



EASYRO® 600

Output (24 hr) 9.600 l
Weight, empty 50 kg
Power consumption 600 W
L/W/H 450/490/558 mm



Our partners



be clean. *stay green.* easymetal.com



easymetal

easymetal GmbH
Resselstrasse 12, 2120 Wolkersdorf
AUSTRIA

be clean. *stay green.* easymetal.com





VIEW MORE

E.KO IONISER®

Deionized water with the lowest conductivity and optimal pH value.



EDM

1501

Suitable for standard applications including aluminium processing.



EDM

1502

Was specially developed for processing carbide, graphite, copper and special materials.



1503

Was specially developed for smoothing already treated water.

- ✓ Ultrapure water
- ✓ Process water
- ✓ Boiler feed water

Your advantages:

- ✓ stable water quality
- ✓ low conductance
- ✓ no hazardous waste
- ✓ long runtime



Technical data

Max. flow rate	40 l/min
Min. flow rate	1 l/min
Max. operating pressure	5 bar
Max. Input conductance	2500 µS/cm
Conductance	< 0,1 µS/cm
Permissible Input pH value	6,5-9,5
Weight	160 kg
Diemensions mm (L/W/H)	660/370/1150
EASY quick coupling	CPC ½"
Equivalent mixed bed resin	approx. 200 liter



KORROS4OP®

Reliable water quality monitoring.

KORROSTOP4.0® measuring device including connection components.

- ✓ For all EDM machines
- ✓ Data logging
- ✓ Network-capable



CONNECT4

Connection components for all EDM machines.

WHEELY

Transport trolley for E.KO IONISER®.



Recommended by well-known machine manufacturers.



VIEW MORE